

Analytical Balances

# AT-R series

Basic Model with Improved Convenience

- Freely set responsiveness or stability
- Connect with a computer via USB or RS232C
- Perform stable measurements in combination with an ionizer




## Features of the AT-R Series

### 1 Easy Settings Enable Responsiveness and Stability to be Freely Changed

Responsiveness becomes very important when weighing fixed amounts of powders and liquids. On the other hand, stability is required when weighing substances in environments subject to drafts or vibrations.

The AT-R balances are equipped with a 5-stage indicator. It is easy to switch between a response focus (R) and a stability focus (S) during measurements.



Response-focused (R)  
for weighing process



Stability-focused (S)  
when vibrations  
become a concern



## 2 Equipped with Two Interfaces: USB and RS232C

The balances are equipped as standard with two convenient interfaces for connection with a computer or PLC (programmable logic controller). Human error can be prevented by direct transfer of weight values to the computer.

●The balances have been shown to operate with the following PLCs from major companies.

- Mitsubishi Electric Q Series      •Keyence KV-8000
- OMRON CJ2 Series                •IDEC FC6A Series



## 3 Addition of an Ionizer Increases Measurement Reliability

The optional STABLO™-AP ionizer (static remover) quickly removes static from samples and containers, without creating a draft. This prevents reproducibility errors and fluctuations in measurement values due to static electricity. The static elimination can be enhanced by placing flasks in the AP Holder (sold separately).



AP Holder



STABLO-AP

### AT-R Series Specifications

Model	ATX324R	ATX224R	ATX124R	ATX84R	ATY324R	ATY224R	ATY124R	ATY64R
Weighing Capacity	320g	220g	120g	82g	320g	220g	120g	62g
Minimum Display	0.1mg							
Pan Size	Approx. 91 mm dia.							
Dimensions	Approx. W213 × D356 × H338 mm							
Weight	Approx. 6.2 kg				Approx. 6.0 kg			
Required Power Supply	AC adapter (input 100-240 V AC, 50/60 Hz, output 12 V, 1 A)							
I/O Terminals	RS232C (D-sub 9P plug), USB device (Type B)							
Calibration Weight	Built-in				External weight			

### Optional Accessories

Description
EP-100 Printer
EP-110 Printer
USB Cable Set
SMK-501 Specific Gravity Measurement Kit
AP Holder
Protective Cover (5 pc set)
AC Adapter (provided as standard with the main unit)

### For Counteracting Static Electricity Ionizer for Electronic Balances

STABLO-AP

Description
STABLO-AP

STABLO is a trademark of Shimadzu Corporation.



**For Research Use Only. Not for use in diagnostic procedures.**

This publication may contain references to products that are not available in your country. Please contact us to check the availability of these products in your country.

Company names, products/service names and logos used in this publication are trademarks and trade names of Shimadzu Corporation, its subsidiaries or its affiliates, whether or not they are used with trademark symbol "TM" or "®". Third-party trademarks and trade names may be used in this publication to refer to either the entities or their products/services, whether or not they are used with trademark symbol "TM" or "®". Shimadzu disclaims any proprietary interest in trademarks and trade names other than its own.

The contents of this publication are provided to you "as is" without warranty of any kind, and are subject to change without notice. Shimadzu does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication.

Shimadzu Corporation  
www.shimadzu.com/an/

© Shimadzu Corporation, 2019  
First Edition: October 2019